# U.S. DEPARTMENT OF LABOR Occupational Safety and Health Administration

# MATERIAL SAFETY DATA SHEET

(Prepared According to 29 CFR 1910.1200)

#### SECTION 1

# IDENTIFICATION

Product Name:

Benchmate #1927

Distributor's Name:

Ricmar Industries, Inc.

Distributor's Address:

889 N. Larch Avenue - Elmhurst, IL 60126

Distributor's Phone Number:

(630) 559-9500 (Inside Illinois)

(800) 323-0779 (Outside Illinois)

Proper Shipping Name:

Consumer Commodity, ORM-D

Effective Date:

10-15-01

#### IDENTITY INFORMATION AND HAZARDOUS INGREDIENTS SECTION 2

Chemical Name:

CAS No .:

TLV:

Naphthenic Oil Kerosene Propane

64742-52-5 8008-20-6 74-98-6

5 mg/m3 as mist Not established 2500ppm

Isobutane n-Butane

75-28-5 106-97-8

Not established mqq008

Ethyl Acetate

141-78-6

400ppm

# SECTION 3

# PHYSICAL DATA

**Boiling Point:** 

<0 to 342° F

Specific Gravity(H, O=1):

 $0.80 \pm 0.05$ 

Solubility in Water:

Nil

Evaporation Rate:

Slower than Ether

Vapor Density(Air=1):

Heavierthan air

pH:

NA

# SECTION 4

# FIRE AND EXPLOSION HAZARD DATA

Flash Point:

140°F

Flash Point(Propellant):

<0°F

Flammable Limits(Propellant): Extinguishing Media:

LEL: 1.0

UEL: 12.8

Special Fire Fighting Procedures:

Use water fog, dry chemical or carbon dioxide. Aerosol cans may rupture when heated.

Unusual Fire and Explosion Hazards:

Heated cans may burst.

## SECTION 5

## REACTIVITY DATA

Stability:

Unstable

Stable

Incompatability (Materials to Avoid):

Conditions to Avoid:

Noneknown.

High temperatures.

Hazardous Decomposition or Byproducts:

In fire, will decompose to carbon dioxide, carbon monoxide

Hazardous Polymerization:

Will not occur

#### STORAGE AND HANDLING INFORMATION SECTION 6

Precautions to be Taken in Handling and Storing:

When spraying more than one half can continuously or more than one can consecutively, use NIOSH approved respirator.

STORE AT TEMPERATURES BELOW 120°F

KEEP AWAY FROM CHILDREN

FOR USE BY TRAINED PERSONNEL ONLY

KEEP AWAY FROM HEAT, SPARKS, OR OPEN FLAME FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY KEEP CONTAINER CLOSED DURING STORAGE

#### SECTION 7

# HEALTH HAZARDS AND FIRST AID

#### Effects of Overexposure:

SKIN: Skin irritant. Will cause defatting of skin. Effects are reversible.

EYES: Eye irritant. Will cause redness and burning sensation.

Effects of overexposure include irritation of respiratory tract, headache, dizziness, INHALATION:

nausea, and loss of coordination. Extreme overexposure may result in

unconsciousness and possibly death.

INGESTION: Aspiration hazard if swallowed.

Prolonged overexposure to solvents in Section 2 may cause adverse effects to the liver, urinary, cardiovascular, and reproductive systems. Repeated and prolonged overexposure to solvents can cause permanent brain and nervous system damage.

#### First Aid Procedures:

Immediately flush exposed area with water for at least 15 minutes. If irritation persists, get SKIN:

medical attention. Remove contaminated clothing and launder before reuse.

EYES: Immediately flush with large quantities of water for at least 15 minutes, lifting upper and lower

eyelids occasionally. Seek medical attention.

INHALATION: Remove person to fresh air. If irritation persists, give oxygen, get medical attention.

INGESTION: DO NOT induce vomiting. Seek medical attention immediately.

Note: Never give anything by mouth to an unconscious or convulsing victim.

Keep person warm and quiet.

# SECTION 8

# SPECIAL PROTECTION INFORMATION

Respiratory Protection: Self-contained breathing apparatus if above TLV limit.

Provide local exhaust to keep TLV of Section 2 ingredients below acceptable limit. Ventilation:

Protective Gloves: None required if spraying.

Eye Protection: As with all cleaners, RICMAR supports employee safety as priority #1. Therefore, we

recommend the use of safety glasses or chemical splash googles.

Other Protective Equipment:

Long sleeves and long pants.

Work/Hygienic Practices:

Do not smoke while using. Wash hands after use.

#### SECTION 9

# SPILL OR LEAK PROCEDURE

Steps To Be Taken In Case Material Is Released or Spilled:

Use absorbent sweeping compound to soak up material. Put into container. Dispose as

hazardous waste.

Waste Disposal Method:

Dispose as hazardous waste in accordance with EPA RCRA.

#### SECTION 10

#### REGULATORY INFORMATION

SARA Title III, Section 313 Components:

None

This information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition. We make no warranties, express or implied, and assume no liability in connection with any use of this information. BENCH-MATE #1927