MATERIAL SAFETY DATA SHEET

Ricmar Industries Inc 889 N. Larch Avenue Elmhurst, IL 60126

GENERAL INFORMATION NUMBER: (630) 559-9500

INFOTRAC: (800) 535-5053

REVISION DATE: December 9, 2005

DATE OF ISSUE: March 1, 2006

I - Product Identification

Water Aide

PRODUCT CODE: 0395

CHEMICAL FORMULATION: Non-ionic wetting agent

NFPA HAZARD IDENTIFICATION SYSTEM: HEALTH: 0

HAZARD RATING:

4 - Extreme;

3 - High;

FLAMMABILITY: 0

REACTIVITY: 0

2 - Moderate;

1 - Slight;

0 - Insignificant

II - Hazardous Ingredients

Values reported as TWA unless noted.

APPROX

OSHA

EPA 40 CFR: ACGIH

CAS#

SUBSTANCE Poly (oxyethylene) nonylphenol

% 15.0-25.0 PEL N/E

TLV N/E

355

9016-45-9

Key:

PEL: Permissible Exposure Limit

TLV: Threshold Limit Value

C: Ceiling level

STEL: Short Term Exposure Limit

N/A: Not Applicable

N/D: Not Determined

N/E: Not Established

Y: Yes

N: No

302: CERCLA List of Hazardous Substances and Reportable Quantities (40 CFR 302.4).

355: SARA TITLE III / List of Extremely Hazardous Substances for Emergency Planning and Notification (40 CFR 355).

372: SARA TITLE III / List of Toxic Chemicals subject to Release Reporting (Community Right to Know) (40 CFR 372).

III - Physical Data

BOILING POINT (4F): N/D

VAPOR PRESSURE (mm Hg): N/D

VAPOR DENSITY (AIR = 1): N/D

SOLUBILITY IN WATER: Soluble

SPECIFIC GRAVITY (WATER = 1): 1.01

VOC CONTENT (% by weight): N/D

EVAPORATION RATE (WATER = 1): N/D

pH: 6.5-7.5

APPEARANCE AND ODOR: Viscous, clear green liquid; mild detergent odor.

IV - Fire and Explosion Hazard Data

FLASH POINT (≤F): None

(TEST METHOD): Closed cup

FLAMMABLE LIMITS IN AIR (VOLUME %)

UPPER: N/A

LOWER: N/A

EXTINGUISHING MEDIA: Water, foam, carbon dioxide, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with full protective gear including self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARD: None.

V - Reactivity Data

STABILITY: Stable

INCOMPATIBILITY: None
CONDITIONS TO AVOID: None

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition may produce oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

VI - Health Hazard Data

ROUTES OF ENTRY INHALATION: EYE CONTACT: X SKIN CONTACT: X INGESTION: X INGREDIENTS THAT ARE CONSIDERED BY OSHA, NTP, IARC TO BE SUSPECTED HUMAN CARCINOGENS: None. EFFECTS OF OVEREXPOSURE

IF IN EYES: Mild irritation.

IF ON SKIN: Possible mild irritation, with prolonged or repeated exposure.

IF SWALLOWED: Possible gastrointestinal irritation, nausea, cramps, vomiting.

IF INHALED: None under normal use.

EMERGENCY AND FIRST AID PROCEDURES

IF IN EYES: Flush eyes and under eyelids with plenty of cool water for at least 15 minutes. If irritation persists, obtain medical attention.

IF ON SKIN: Wash with soap and water. If irritation persists, obtain medical attention.

IF SWALLOWED: Contact physician or poison control center immediately. Give affected person several glasses of water and induce vomiting. Never give anything to an unconscious person.

IF INHALED: Remove person to fresh air.

VII - Spill or Leak Protection

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spill. Soak up spilled material with inert absorbent material or flush away with water.

WASTE DISPOSAL METHOD: Consult local environmental authorities for disposal in accordance with state and local regulations.

VIII - Special Protection Information

RESPIRATORY PROTECTION: Not required under normal use.

VENTILATION

LOCAL: Recommended

MECHANICAL: Not required

PROTECTIVE GLOVES: Chemical resistant.

EYE PROTECTION: Safety glasses.

OTHER PROTECTIVE EQUIPMENT: None.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store in a cool, dry place. Keep container tightly closed when not in use.

OTHER PRECAUTIONS: Keep out of reach of children.

IX - Transportation Information (ground transportation only)

DOT PROPER SHIPPING NAME: None

DOT CLASS: None

DOT ID NUMBER: None

DOT PACKING GROUP: None

The shipping information listed above applies only to non-bulk (< 119 gallons) containers of this product. This product may have more than one proper shipping name depending on packaging, product properties, & mode of shipment. If any alteration of packaging, product, or mode of transportation is further intended, different shipping names and labeling may apply.

REVISION DATE: December 9, 2005

Prepared by: Technical Dept.

DATE OF ISSUE: March 1, 2006

This information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Ricmar Industries Inc assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material such vendees or users assume all risks associated with the use of this material.