MATERIAL SAFETY DATA SHEET COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200)

SECTION I · PRODUCT IDENTIFICATION

		SECTION	I • PRODUCT II	DENTIFICATIO	ON			
Product Name: Contro Mist Organic Degreaser Product Number: 413 Product Type: AEROSOL			Date Prepared: 11/26/2007			HMIS Rating (Based on Aerosol Conc.): 0-Minimal 1-Slight 2-Moderate 3-Serious 4-Extreme		
Formula:	Proprietary					HEALTH:		1
Supplier's Name:	Ric Mar Industries, Inc.		Information Phone:	(630) 559-9500		FLAMMABILITY:		2
Supplier's Address: 889 N. Larch Ave., Suite 200, Elmhurst, IL DOT Ship Description: Consumer Commodity, ORM-D		IL 60126	L 60126 Emergency Phone: (800) 535-5053			PHYSICAL HAZARD: Personal Protection:		0
								В
		-		-	Chin	Coroineron	DEI	TLV-TWA
CHEMICAL NAME	<u>u</u>	CAS <u>#</u>	<u>%WT</u>	<u>313/Chem</u>	<u>Skin</u>	Carcinogen	PEL	ILV-IWA
Citrus Terpene	5	989-27-5	40 - 50	NO	NO	NO	N/E	N/E
Carbon Dioxide	1	24-38-9	1 - 5	NO	NO	NO	5000 ppm	5000 ppm
		SEC	TION III · PHYSI	CAL DATA				
Aerosol Concentrate	:							
Boiling Point:	302 ℉		Specific Gravity (H2	2O=1)@70°F:	0.86			
pH:	N/A		Solubility In Water:	, -	Insoluble			
Appearance/Odor:	Clear, light amber liquid with citrus odor		Vapor Density(Air=	1):	>1			
Total Contents:								
Total VOC %:	47.05%		Vapor Pressure (ca	n∵nsia @72°F):	80 psi			
	11.0070			iii, poig @ / E i /.	00 001			
	S	ECTION I	V · FIRE AND E	XPLOSION D	ΔΤΔ			
Flash Point (Conc.):	115℉ (T.O.C)	Flammability (as per CSMA Fla				ne Projection Test):	Flammable Sp	rav
Extinguishing Media: Foam, CO2, Dry Media								,
Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.								
Unusual Fire and Explo	osion Hazards: Exposure to temperature at	bove 120° F	may cause bursting.					
		SECT						
Stability:	Material Stable.	SEC.		Hazardous Polyn	nerization:	Will not Occur.		
	contact with strong oxidizing agents,			Tiazaidous i olyn	nenzation.	will not occur.		
	tion Products: Carbon Dioxide, Carbon Mo	onoxide						
		SECTION			NG			
KEEP OUT OF REACH OF CHILDREN. For Industrial and Institutional use only.			VI- STONAGE	NFPA Code 30B	-	Level 3 Aerosol.		
						200010710100001.		
	a away from heat or open flame.							
Do not store at temper								
		0507101						
		SECHO	Ι VII . ΗΕΔΙ ΤΗ .					

SECTION VII · HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE:

Eyes: May cause moderate to severe irritation.

Skin: Frequent or prolonged contact may cause irritation, drying and defatting of skin, and dermatitis. May aggravate existing skin conditions.

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Frequent or prolonged exposure may cause irritation to the upper respiratory tract, coughing, dizziness, nausea and headache.

Ingestion: Harmful if swallowed. Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause lung injury.

FIRST AID PROCEDURES:

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. Skin: Wash with soap and water. If irritation persists seek medical attention.

Inhalation: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

Ingestion: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII · SPECIAL PROTECTION DATA

Respiratory Protection: None needed for proper use in accordance with label directions.

Ventilation: Provide local exhaust to keep concentration of Section II ingredients below acceptable limits.

Protective Gloves: Use chemical resistant gloves if hand contact will be made.

Eye Protection: Always wear safety glasses or chemical proof goggles when working with chemicals.

SECTION IX - SPILL OR LEAK PROTECTION

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK: Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD: Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

N/A= NOT APPLICABLE · N/E=NOT ESTABLISHED · N/D=NOT DETERMINED · <=LESS THAN · >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.