

HMIS RATINGS:
 Health: 2
 Flammability: 2
 Reactivity: 0
 Personal Protection: G

Section 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Trade Name: GREASE-OUT II 5 GAL PAIL
 Chemical Family: Solvent Degreaser
 Company Identification: RIC MAR CHEMICALS INC.
 889 NORTH LARCH SUITE 200
 ELMHURST, IL 60126

Emergency Phone: 800-535-5053
 Date Prepared: 10/31/10
 MSDS Number: 6072

Section 2: COMPOSITION, INFORMATION ON INGREDIENTS

CAS NUMBER	CHEMICAL NAME	% BY WGHT.	OSHA PEL/ ACGIH TLV	SARA 302/304(1)*	SARA 313 (2)*	STATE INFO(3)(4)	CERCLA RQ
8008-20-6	Kerosene	< 70.0	n/e / n/e	NO	NO	NO	
64742-95-6	Light Aromatic Solvent Naphtha	< 25.0	300 ppm / 300 ppm	NO	NO	NO	
95-63-6	1,2,4-TrimethylBenzene	< 7.0	25 ppm	NO	YES	NO	
98-82-8	Cumene	< 2.0	50 ppm	NO	YES	NO	5000 lbs
628-63-7	Amyl Acetate	< 2.0	100 ppm /	NO	NO	NO	5000 lbs

* See Section 15 for more information

n/e = none established - n/a = not applicable

Section 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. Combustible. Keep away from heat and flame. Harmful or fatal if swallowed. Aspiration hazard. Vapor harmful. Harmful if absorbed through skin. Can cause nervous system depression. Clear, red liquid with solvent odor.

Primary Route of Entry: Skin contact/absorption, inhalation, eye contact

Acute/Potential Health Effects:

EYES: May cause mild to moderate eye irritation. Symptoms include stinging, tearing and redness and swelling of the conjunctiva.

SKIN: May cause mild skin irritation. Prolonged or repeated contact may dry the skin. Absorption from prolonged or massive skin contact may cause poisoning.

INHALATION: Avoid breathing vapors or mists. May cause dizziness, nausea, headache or loss of consciousness.

INGESTION: Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

Signs and Symptoms of Overexposure: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of material through the skin may include:

Trade Name: GREASE-OUT II 5 GAL PAIL

MSDS Number: 6072

stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects: No data.

Reproductive/Developmental Information: This product contains components which may cause adverse reproductive and/or developmental effects.

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

Section 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

SKIN: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

INGESTION: Seek medical attention immediately. Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Do not leave individual unattended.

Section 5: FIRE FIGHTING MEASURES

Flash Point: 110 degrees F (T.O.C. Method)

Extinguishing Media: Dry chemical, CO2 or foam is recommended.

Special Fire Fighting Instructions: Wear a self contained breathing apparatus with a full face-piece operated in the positive pressure demand mode with chemical resistant personal protective equipment.

Section 6: ACCIDENTAL RELEASE MEASURES

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Absorb spill with inert material (e.g. dry sand, earth). Eliminate all ignition sources. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

Section 7: HANDLING AND STORAGE

Follow all MSDS/label precautions even after container is emptied because they may contain product residues. Use with adequate ventilation. Do not get in eyes, on skin or on clothing. Store in a cool, dry place. Keep container closed when not in use. Keep out of reach of children.

Section 8: EXPOSURE CONTROLS and PERSONAL PROTECTION

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene), clothing and boots.

Trade Name: GREASE-OUT II 5 GAL PAIL

MSDS Number: 6072

Respiratory Protection: When respiratory protection is required, use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 and ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance and Odor: Clear, red liquid with solvent odor

pH Concentrate: n/a

Solubility in Water: Insoluble

Vapor Pressure [mmHg]: n/e

Evaporation Rate (Butyl Acetate=1): 0.2

Vapor Density [Air=1]: n/e

Specific Gravity [H2O=1]: 0.82

Boiling Point: > 280F

Section 10: REACTIVITY

Stability: Stable

Hazardous Polymerization: Will not occur

Conditions to avoid: High temperature

Hazardous Decomposition Products: CO, CO2, NOx

Incompatibility: Strong acids, bases and oxidizers

Section 11: TOXICOLOGICAL INFORMATION

No data.

Section 12: ECOLOGICAL INFORMATION

No data

Section 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

Section 14: TRANSPORTATION INFORMATION

D.O.T. Shipping Name / Class:

Not regulated for ground domestic shipments.

Section 15: REGULATORY INFORMATION

U.S. Federal Regulations:

TSCA (Toxic Substances Control Act): The intentional ingredients of product are listed.

Title III Section 311/312 Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic (X) Fire (X) Pressure () Reactive () Not Applicable ()

Trade Name: GREASE-OUT II 5 GAL PAIL

MSDS Number: 6072

(1) Title III Section 302/304 Extremely Hazardous Substances - 40 CFR 355 Appendix A

(2) Title III Section 313 Toxic Chemicals - 40 CFR 372.65

If indicated under Section 2 of this MSDS, this product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right to Know Act of 1986. This information must be included in all MSDS that are copied and distributed for this material.

RCRA Status: Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes a hazardous waste it would be assigned RCRA Code(s)

D001

State and Local Regulations: Certain states maintain their own ingredient lists which differ slightly from the Federal standards. If indicated under Section 2 of this MSDS, states listed below may have regulations on ingredients contained in this product. Check with your state for any additional regulations.

(3) California proposition 65 (Safe Drinking Water & Toxic Enforcement Act of 1986)

(4) Massachusetts (Hazardous Substance Disclosure by Employers)

Section 16: OTHER INFORMATION

This information was compiled from current manufacturer's MSDS's of the component parts of the product.

Disclaimer: The Manufacturer believes that the information contained in the Material Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.
