

=====
MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to
comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.
=====

PRODUCT NUMBER: 203
IDENTITY: SNAPPY 20A Revision Date: 01/14/2009

Section I

Manufacturer's Name: RICMAR INDUSTRIES Telephone Numbers:
Address: 889 N. LARCH AVE., SUITE 200 Emergency:
800/255-3924
ELMHURST Information:
State: IL Zip Code: 601261109 630/559-9500

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 0 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the
ingredients contained in this product are listed on the TSCA inventory.)
=====

Table with 6 columns: Name, Cas No., OSHA PEL, ACGIH TLV, OTHER LIM, %. Row 1: PROPANE/N-BUTANE, 68476-86-8, N/A, 1000ppm, N/A, ____.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS
=====

Boiling Point: 212 + Specific Gravity (water=1) 1.02
Vapor Pressure(mm Hg) 17.5 Melting Point: N/A
Vapor Density(AIR=1) >1 Evaporation Rate: <1
Solubility in Water: 100% (Butyl Acetate=1)
Appearance and Odor: CLINGING FOAM, NO DISTINCT ODOR

Section IV: FIRE AND EXPLOSION HAZARD DATA
=====

Flash Point(Method Used):N/A Flammable Limits: LEL: UEL:
Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE, AND FOAM
Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPARATUS IS
ALWAYS RECOMMENDED WHEN FIGHTING FIRES.

Unusual Fire and Explosion Hazards: CONTENTS UNDER PRESSURE. EXPOSURE TO
TEMPERATURES ABOVE 120F MAY CAUSE BURSTING.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 203

Stability: Unstable: Conditions to avoid:
Stable: X TEMPERATURES ABOVE 120F
Incompatibility (Materials to Avoid): NONE KNOWN

Hazardous Decomposition or Byproducts: CARBON DIOXIDE AND CARBON MONOXIDE

Hazardous Polymerization: May Occur: Will Not Occur: X
Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES
Health Hazards (Acute and Chronic):
INHALATION: EXCESSIVE INHALATION MAY CAUSE DIZZINESS. EYES: MAY CAUSE
IRRITATION OR REDNESS. SKIN: MAY CAUSE SLIGHT IRRITATION. INGESTION: MAY
CAUSE NAUSEA OR VOMITING.
Carcinogenicity: NTP: NO IARC Monographs: NO OSHA Reg: NONE
Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: SKIN SENSITIVITY,
CHEMICAL ALLERGIES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. EYES:
FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH AFFECTED AREA WITH SOAP AND
WATER. INGESTION: DRINK LARGE QUANTITY OF WATER. IN ALL CASES, SEEK MEDICAL
ATTENTION IF IRRITATION PERSISTS.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG
OR ABSORBENT CLAY MATERIAL OR TOWEL.

Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE,
AND LOCAL GUIDELINES. DO NOT PUNCTURE OR INCINERATE CONTAINER. DO NOT REUSE
CONTAINER. WRAP CONTAINER IN PAPER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE BURSTING.

Other Precautions: NONE

Section VIII: CONTROL MEASURES

Respiratory Protection: NONE REQUIRED
Ventilation: Local Exhaust: ADEQUATE
Mechanical: N/A Special: N/A
Other: N/A
Protective Gloves: N/A
Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.
Other Protective Clothing or Equipment:
N/A
Work/Hygienic Practices:
WASH HANDS WITH S