SECTION 1: Product an	Id company identification			
Product name	: Select			
Use of the substance/mixture	: Aerosol			
Herbicide				
Product code	: 8363			
Company	: Ricmar Industries Inc 747 N Church RdSuite G-4 Elmhurst, IL 60126 - USA T (630) 559-9500			
Emergency number	: INFOTRAC CHEMICAL EMERGENCY RESPONSE: (800) 535-5053			
SECTION 2: Hazards id	entification			
2.1. Classification of the su	bstance or mixture			
Classification (GHS-US)				
Acute Tox. 4 (Oral) H Acute Tox. 3 (Inhalation:gas)	H280 H302 H331 H371			
Full text of H-phrases: see sect	tion 16			
2.2. Label elements				
GHS-US labeling				
Signal word (CHS-US)	GHS04 GHS06 GHS08			
Signal word (GHS-US) Hazard statements (GHS-US)	: Danger : Contains gas under pressure; may explode if heated			
	Harmful if swallowed Toxic if inhaled May cause damage to organs (kidneys, liver)			
Precautionary statements (GHS	S-US) : Do not breathe mist, spray, vapors Avoid breathing spray, mist, vapors Wash thoroughly after handling Do not eat, drink or smoke when using this product Use only outdoors or in a well-ventilated area If swallowed: Call a POISON CENTER, a doctor if you feel unwell If inhaled: Remove person to fresh air and keep comfortable for breathing Call a POISON CENTER, a doctor Specific treatment (see First aid measures on this label) Rinse mouth Store in a well-ventilated place. Keep container tightly closed Store locked up Protect from sunlight. Store in a well-ventilated place Dispose of contents/container to comply with local/regional/national/international regulations			
2.3. Other hazards				
Other hazards not contributing classification	to the : Contains gas under pressure; may explode if heated.			
2.4. Unknown acute toxicity	/ (GHS US)			
Not applicable				

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
butane	(CAS No) 106-97-8	1 - 5	Flam. Gas 1, H220 Compressed gas, H280
propane	(CAS No) 74-98-6	1 - 5	Flam. Gas 1, H220 Compressed gas, H280
Dimethylamine Salt of 2,4-Dichlorophenoxyacetic Acid	(CAS No) 2008-39-1	0.326	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 2, H373
MCPP DMA Salt	(CAS No) 66423-09-4	0.164	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318
2,4-DP DMA Salt	(CAS No) 104786-87-0	0.161	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332

4.1. Description of first aid measure	S
First-aid measures general	: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Artificial respiration and/or oxygen if necessary. Call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Take off contaminated clothing. Consult a doctor/medical service. Wash immediately with lots of water (15 minutes)/shower.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Get immediate medical advice/attention. Drink plenty of water. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.
4.2. Most important symptoms and	effects, both acute and delayed
Symptoms/injuries	: Harmful if swallowed. May cause damage to organs through prolonged or repeated exposure. Toxic if inhaled.
Symptoms/injuries after inhalation	: Toxic if inhaled. Symptoms similar to those listed under ingestion. Headache. Dizziness. Unconsciousness.
Symptoms/injuries after skin contact	: Contact during a long period may cause light irritation.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion	: Harmful if swallowed. Nausea. Vomiting. Abdominal pain.

4.3. Indication of any immediate medical attention and special treatment needed

- Treat symptomatically.
- **SECTION 5: Firefighting measures** Extinguishing media 5.1. Suitable extinguishing media : Adapt extinguishing media to the environment. Dry chemical powder. Carbon dioxide. Foam. Water spray. Water fog. Special hazards arising from the substance or mixture 5.2. Fire hazard Under fire conditions closed containers may rupture or explode. Explosion hazard Contains gas under pressure; may explode if heated. : Reactivity Thermal decomposition may produce oxides of carbon and nitrogen. hydrogen chloride. : Advice for firefighters 5.3. : Exercise caution when fighting any chemical fire. Avoid (reject) fire-fighting water to enter **Firefighting instructions** environment. Take account of environmentally hazardous firefighting water. Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. SECTION 6: Accidental release measures 6.1. Personal precautions, protective equipment and emergency procedures

General measures		 Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk. Stay upwind/keep distance from source. 			
6.1.1. For non-emergency	personnel				
Protective equipment : Do not enter without an appropriate protective equipment.					
Emergency procedures : Advice local authorities if considered necessary.					
Date of issue: 9/23/2015	Revision date: 05/25/2015	Version: 1.0	P GHS SDS	Page 2 of 7	

Safety Data Sheet

6.1.2. For emergency responde	ers
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.
6.2. Environmental precautio	ns
Prevent entry to sewers and publ suitable container.	ic waters. Do not allow to enter drains or water courses. Absorb and/or contain spill with inert material, then place in
6.3. Methods and material for	containment and cleaning up
For containment	: Dam up the liquid spill. Collect spillage.
Methods for cleaning up	: Liquid spill: dam up with sand/earth. Carefully collect the spill/leftovers. Notify authorities if product enters sewers or public waters.
Methods for cleaning up 6.4. Reference to other section	enters sewers or public waters.

7.1. Precautions for safe handling	
Additional hazards when processed	: Do not puncture, incinerate or crush.
Precautions for safe handling	: Avoid contact with skin, eyes and clothing. Avoid breathing spray, mist, vapors. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Clean contaminated clothing. Do not allow people (other than applicator) or pets on treatment area during application. Do not enter treatment areas until spray has dried.
Hygiene measures	: Always wash hands after handling the product. Wash contaminated clothing before reuse. Use good personal hygiene practices.
7.2. Conditions for safe storage, inc	cluding any incompatibilities
Technical measures	: Do not puncture, incinerate or crush.
Storage conditions	 Protect from freezing. Keep only in original container. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
ACGIH	ACGIH STEL (ppm)	1000 ppm	
propane (74-98-6)			
ACGIH	ACGIH TWA (ppm)	1000 ppm	
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm	

8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment

Gloves. Protective clothing. Protective goggles. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

0.1. Information on basic physical and chemical properties			
Physical state	: Liquid		
Appearance	: Aerosol. Foam.		
Odor	: No data available on odor		
Odor threshold	: No data available		
рН	: 9-10		

:

Safety Data Sheet

Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No flame extension with method ASTM D3065-72
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.008 g/ml
Solubility	: Soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: 5%

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition may produce oxides of carbon and nitrogen. hydrogen chloride.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Heat. Open flame.

10.5. Incompatible materials

Strong oxidizing agents. alkalis. acids.

10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide. HCl. Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

: Oral: Harmful if swallowed. Inhalation:gas: Toxic if inhaled.

Date of issue: 9/23/2015	Revision date: 05/25/2015	Version: 1.0	P GHS SDS	Page 4 of
Germ cell mutagenicity	: Not classified			
Respiratory or skin sensitization	: Not classified.			
	pH: 9 - 10			
Serious eye damage/irritation	: Not classified			
	pH: 9 - 10			
Skin corrosion/irritation	: Not classified			
LD50 oral rat	500 - 2000 m	g/kg		
MCPP DMA Salt (66423-09-4)				
LD50 dermal rat	> 2000 mg/kg	3		
LD50 oral rat	567 mg/kg			
2,4-DP DMA Salt (104786-87-0)			

Safety Data Sheet

Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
Specific target organ toxicity (single exposure)	:	May cause damage to organs (kidneys, liver).
Specific target organ toxicity (repeated exposure)	:	Not classified
Aspiration hazard		: Not classified
Symptoms/injuries after inhalation		: Toxic if inhaled. Symptoms similar to those listed under ingestion. Headache. Dizziness. Unconsciousness.
Symptoms/injuries after skin contact		: Contact during a long period may cause light irritation.
Symptoms/injuries after eye contact		: Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion		: Harmful if swallowed. Nausea. Vomiting. Abdominal pain.
Likely routes of exposure		: Skin and eves contact.;Inhalation;Ingestion.

SECTION 12: Ecological information

12.1. Toxicity		
No additional information available		
12.2. Persistence and degradability		
No additional information available		
12.3. Bioaccumulative potential		
No additional information available		

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods	: Do not puncture, incinerate or crush.	
Waste disposal recommendations	: Do not pierce or burn, even after use.	
Additional information	: Do not re-use empty containers.	

SECTION 14: Transport information

Department of Transportation (DOT)	
Transport document description	: UN1950 Aerosols (non-flammable, (each not exceeding 1 L capacity)), 2.2
UN-No.(DOT)	: UN1950
Proper Shipping Name (DOT)	: Aerosols
	non-flammable, (each not exceeding 1 L capacity)
Transport hazard class(es) (DOT)	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
Hazard labels (DOT)	: 2.2 - Non-flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	: None
DOT Packaging Bulk (49 CFR 173.xxx)	: None
DOT Special Provisions (49 CFR 172.102)	:
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A
DOT Vessel Stowage Other	: 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials

Safety Data Sheet

- Additional information
- Other information

: This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.150.

ADR	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: UN1950
Proper Shipping Name (IMDG)	: Aerosols, Non-flammable
Class (IMDG)	: 2.2 - Non-flammable, non-toxic gases
Air transport	
UN-No.(IATA)	: UN1950
Proper Shipping Name (IATA)	: Aerosols, non-flammable
Class (IATA)	: 2.2 - Gases : Non-flammable, non-toxic

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

butane (106-97-8)

Not listed on SARA Section 313 (Specific toxic chemical listings)

propane (74-98-6)

Not listed on SARA Section 313 (Specific toxic chemical listings)

California Proposition 65 - This product does not contain a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.

CAUTION. Harmful if swallowed. Harmful if absorbed through skin. Harmful if inhaled. Causes moderate eye irritation. Avoid contact with eyes, skin or clothing. Avoid breathing spray mist or vapor. Wear long-sleeved shirt, long pants, shoes, socks and chemical-resistant gloves made of any waterproof material.

SECTION 16: Other information

Training advice

: Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Gas 1	Flammable gases Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 2	Specific target organ toxicity (single exposure) Category 2
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed

Safety Data Sheet


H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H332	Harmful if inhaled
H371	May cause damage to organs
H373	May cause damage to organs through prolonged or repeated
	exposure

NFPA health hazard NFPA fire hazard

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard NFPA reactivity

2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.